

Mudfords

SUPPLIERS TO INDUSTRY, TRANSPORT AND CONSTRUCTION

Mudfords Ltd, Registered in England No. 2632883 Registered Office: 400 Petre Street, Sheffield, South Yorkshire S4 8LU
E-mail: sales@mudfords.co.uk Website: www.mudfords.co.uk

TECHNICAL SPECIFICATIONS

Debris Netting – Standard & Flame Retardant

Construction	Knitted mono-filament polyethylene yarn.
Eyelets	Reinforced black eyelet band along each edge and double eyelet band in centre, with eyelets repeating at approximately 10cm centres.
Usage	Used to clad scaffolding. Debris netting will assist in reducing the risk of accidents to the work force and general public caused by falling and wind blown debris by acting as efficient containment net. It will provide some protection from wind and rain.
Installation instructions	Install to BS8093.
Flammability	Flame retardant quality meets the flammability requirements of BS7955:1999 and LPS1215 – small flame, medium flame and flammable liquid test.
BS7955:1999	Impact test – passed. Puncture – passed.
Weight	80gsm.
Roll widths	2 metre or 3 metre.
Roll length	50 metres
Colour availability	2m width – blue, green, black, red, yellow, orange. 2m width FR – white. 3m width – blue, green. 3m width FR – white.

400 Petre Street
Sheffield
S4 8LU
Tel: 0114 243 3033
Fax: 0114 244 4536



Mudfords Ltd Sheffield
Cert No 9407



Alverthorpe Road
Wakefield
WF2 9NT
Tel: 01924 364 771
Fax: 01924 291 725